







Comfort-Line Pressing Unit ACO152

Compact and high-performance efficiency







 Metal systems up to 32 mm
(Australian standard)
Plastic systems up to 40 mm

 Rechargeable battery
(Li-Ion)

 One-Hand-Operation

 Status indication
with LED Display

 Rotatable
Head

-  Powerful Milwaukee Lithium-Ion batteries for reliable performance
-  Redundant switch-off and press force control with LED indication
-  Automatic pressing cycle
-  Safe handling with slipproof rubberized housing and ergonomic design
-  Rotatable head
-  Manual release valve



Press jaws PB15

novopress
because quality matters

Comfort-Line Pressing Unit ACO152

Compact and high-performance efficiency

The pressing unit ACO152 has many valuable features to make working easier, faster and safer. The LED signal located under the transparent start button gives information about the battery and the status of the pressing unit or occurred failures.

Scope of application

- Drinking water-, gas- and heating installations, industry and commercial applications and many more
- Suitable for all authorized jaws of other system manufacturers in the market*
- All common profiles for metal and plastic systems available

Accessories

- Press jaws PB15
- Charger available in many worldwide power supply specifications
- Batteries with different capacities available



The LED signal located under the transparent start button gives information about the battery and the status of the pressing units or occurred failures.

Novopress quality and service

Comfort-Line

- Battery-empty-detection
- Error display
- Device information through the LED indication under the start button
- Automatic pressing cycle

Maintenance and service

- Qualified service on site thanks to international service network
- Extended warranty (further information at www.novopress.de)

Technical Data ACO152

Dimensions**:	Metal pipe up to 32 mm (Australian standard)/ Plastic pipe up to 40 mm
Weight incl. Battery:	1.8 kg
Length:	319 mm
Width:	96 mm
Height:	70 mm
Power consumption:	240 W
Piston force:	24 kN
Piston stroke:	30 mm
Battery:	12 V / 1.5 Ah Li-Ion Milwaukee 12 V / 3.0 Ah Li-Ion Milwaukee
Battery capacity***:	40 - 180 press cycles
Charging time:	30 / 60 min.

* for binding information please request your system manufacturer
** system-dependant
*** depending on material, dimension and battery type

We reserve the right to make technical modifications.

novopress

Novopress GmbH & Co. KG
Scharnhorststraße 1 · D-41460 Neuss
Tel.: +49(0)2131-288-0 · Fax: +49(0)2131-288-55
www.novopress.de · E-Mail: verkauf@novopress.de